

OPTIMIZED EARTHWORK PLANNING METHODOLOGY FOR LAND DEVELOPMENT PROJECTS

Hyeonggi Baek and Jongwon Seo*

Department of Civil and Environmental Engineering, Hanyang University, Seoul, Korea

* *Corresponding author (jseo@hanyang.ac.kr)*

ABSTRACT: An earthwork for land development projects, which possesses around 20% of the total project cost, consists mainly of simply repetitive tasks such as loading, hauling, dumping, and returning and depends largely on heavy construction machines. The goal of earthwork planning is to minimize the project cost and duration by determining soil allocation, equipment configuration, and haul route. Due to the absence of programs or guidelines for earthwork planning, planners rely heavily on their experiences for planning. Subjective decisions can cause problems such as repetitive works, difficulties in finding solutions, and considerable working time. This paper presents the earthwork planning model using Simulated Annealing algorithm which is a stochastic optimization algorithm. Interviews with planners were conducted to investigate current earthwork planning process and planners' heuristics. It is found that the objective of earthwork planning is to minimize earthwork cost by balancing soil volume and minimizing hauling distance. In order to reflect collected planners' rules of thumb, three objective functions (balancing cut-fill volume, compactness, and constructability) were framed and case study was conducted to verify the applicability of the proposed model.

Keywords: *Earthwork Planning, Optimization, Simulated Annealing Algorithm, Land Development Project*

1. INTRODUCTION

Earthwork tasks for site development projects repeat simple works; loading-hauling-dumping-returning. When planning earthworks, planners depend on their experiences due to the lack of guidelines or planning tools. This paper proposes an earthwork planning model which aims to assist planners in finding the optimized solution.

This paper consists of three sections. First, planning process and planners' heuristics were investigated through literature reviews and interviews with planners. Second, the model was established using Simulated Annealing (SA) algorithm. Finally, case study was conducted to verify the applicability and usability of the model.

2. EARTHWORK PLANNING

Current earthwork planning process and planners' heuristics or "rules of thumb" were investigated. In Korea, earthwork planners use a program namely DAS provided by Korea Land and Housing Corporation. It divides the field into 4m by 4m grids, calculates net soil volume, and

determines cut and fill areas [1]. Based on the result, planners devise an earthwork plan. By reviewing literatures [2], [3], [4] and interviewing with planners, it was established that the goal of planning is to balance cut-fill volume and minimize the hauling cost. When estimating hauling cost, planners use the average hauling distance.

$$\frac{\sum_{i=1}^n \sum_{j=1}^m D_{ij} \times Q_{ij}}{\sum_{i=1}^n \sum_{j=1}^m Q_{ij}}$$

Equation (1)

where D_{ij} : hauling distance from cut i to fill j
 Q_{ij} : soil quantity from cut i to fill j

3. EARTHWORK PLANNING MODEL

Earthwork planning model was established using Matlab due to its merit to form the field into a shape of a matrix and the frame of earthwork planning model was configured in three parts.

First, based on imported data from DAS, districting algorithm generates a new alternative. It was framed to divide the site into fixed number of districts and to avoid

