

An integrated 5D tool for quantification of construction process emissions and accident identification

J.K.W. Wong^a, H. Li^a, G. Chan^a, H. Wang^a, T. Huang^a and E. Luo^a

^aDepartment of Building and Real Estate, the Hong Kong Polytechnic University, Hong Kong
E-mail: johnny.wong@polyu.edu.hk, heng.li@polyu.edu.hk, greg.chan@connect.polyu.hk, 1989whr@gmail.com,
huangting001@gmail.com, eric.xiaochun.luo@polyu.edu.hk

Abstract -

The environmental and safety performance of construction sites are increasingly regarded as critical factors that need to be monitored for the successful completion of construction projects. Research has also repeatedly highlighted the need to minimise the carbon footprint of the construction process and enhance the capacity of the project team and on-site workers in detecting and avoiding potential construction site hazards. However, a multi-dimensional visualisation technology that would allow project teams to simulate potential carbon emissions from construction plant and equipment and to detect potentially ‘dangerous’ locations on a construction site is currently lacking. This paper illustrates an integrated 5D model that uses virtual prototyping technologies to quantify carbon emissions, simulate the pattern of emissions from the overall construction process and identify potential ‘black spots’ of site hazards at the planning stage. The proposed 5D BIM based pro-active construction management system (PCMS) can help to detect potential sources of danger to on-site workers and provides pro-active warnings to prevent fatal accidents caused by falling or being struck by moving objects. A public housing project developed by the Hong Kong Housing Authority is used as a case study to demonstrate the integration of the emission prediction visualisation and accident detection tool into the BIM. The proposed tool demonstrates the utilisation of BIM technology to promote pro-active carbon mitigation and safety performance strategies.

Keywords -

Carbon emissions; construction process; virtual prototyping; construction accidents

1 Introduction

Environmental and safety performance, together with ‘cost’, ‘time’ and ‘quality’, are currently

considered to be five key indicators of construction project performance [1]. In recent decades, the construction industry has also been seen to play an increasingly important role in mitigating greenhouse gas emissions due to the ‘fuel-intensive nature and large share of carbon emissions of the industry’ [2]. However, construction sites are also regarded as the most risky and accident-prone workplaces. A poor site safety performance can result in legal liability for the contractors and clients as well as project financial loss and contract delay. In Hong Kong, for example, two major causes of injury on construction sites are striking against or being struck by moving objects, and being struck by moving vehicles [3 and 4]. The capacity to detect and avoid potential hazards will help to improve the safety performance of construction sites.

The current construction boom in Hong Kong presents challenges with regards to the potential for increased carbon emissions and on-site accidents [5]. Accordingly, there is a growing need to reduce the carbon emissions and enhance the safety of the working environment in the sector. A better visualisation of the carbon emissions from construction activities and potential on-site accident ‘black spots’ would help improve the environmental and safety performance of the industry. This paper reports the development and application of a virtual prototyping (VP) based 5D tool (i.e. three-dimensional model, emissions data and site real-time location data) for estimating the possible emissions from construction projects and detecting potential on-site accident black-spots. A public housing project in Hong Kong is used to demonstrate the application of the tool

2 The integrated emissions and hazard detection tool

Over the past decade, numerous studies have examined the use of IT technologies in quantifying the emissions from construction processes and detecting potential on-site hazards. Most of the current research on the prediction and visualisation of construction site emissions has been led by universities and research

centres in the US [6-17]. Despite these efforts, most of the existing emissions visualisation and quantification models are still in the early stages of development and are limited to regional applications. Much of the existing research also focuses on specific construction trades or activities, such as concreting, earthwork and lifting. Moreover, limited research has focused on developing tools that provide a more holistic estimation of emissions from all of the construction activities in a project [2]. Hajibabai et al. [10] have highlighted the need for a more comprehensive tool to analyse and visualise the carbon emissions from construction sites.

With regards to site safety detection, advanced positioning systems such as the radio frequency identification device (RFID), global positioning system (GPS), ultra wide-band (UWB) and wireless local area network (WLAN) allow real-time monitoring of the location of construction workers, equipment and materials [18]. The purpose of these positioning technologies for safety management is to prevent workers from entering hazardous areas such as floor openings, floor edges and equipment operation areas [18-24]. However, because of their varying levels of accuracy, the different positioning systems have the potential to generate false alarms.

The visualisation tool presented in this paper is implemented in four steps [2]: i) collect the general project and equipment data; ii) develop the plant operation plans; iii) identify the predicted emission quantities and setup the emission estimation model (PEEM); and iv) construct a four-dimensional virtual prototype and import the emissions data. First, a series of activities, each of which have a defined duration, are linked with the construction plant, components and resources [2]. Information, including the operating hours of the equipment and plant based on the site equipment operation plan, is then acquired to predict the emissions from the construction process [2]. Details of the VP emissions visualisation model can be found in [2]. By linking the 3D models (Revit-based software) and the construction project schedules (MS Project files) using Autodesk NavisWorks, the tool is able to model the 4D construction schedule and allows real-time and whole-project simulation. The 5D BIM tool also includes a pro-active construction management system (PCMS), which can assist construction site workers in detecting potential sources of danger and provide pro-active warnings on potential hazards. The PCMS comprises two sub-systems: a real-time location system (RTLS) and a virtual construction simulation system (VCS). Figure 1 depicts the typical three-tier web-based application structure (presentation layer + business layer + data layer) of the PCMS.

The real-time location system (RTLS) can be divided into two parts: the real-time location network and the real-time location engine. The ‘network’ is constructed using small hardware devices which serve as tags, which

are designed to be mounted onto helmets and moving objects, and anchors, which are designed to be fixed in static locations to serve as reference points. The anchors locate the tags. The system uses the time of flight (TOF) based location schema. The tags also help to alert construction workers by vibrating and/or emitting a specific sound when they are exposed to a particular danger. An important task in location-based construction safety risk monitoring is to define the relevant dangers (e.g., static dangers and dynamic dangers) in the models and to calculate the relative distances between workers. The real-time location engine is designed with three functions: managing the location network, calculating the tag locations and sending alert signals to the tags. A network may be composed of dozens of tags and anchors. When the ranging results are received, the location engine uses an effective algorithm to calculate the tag positions and sends the positions to the application server for the virtual construction simulation and safety management.




Figure 1. System architecture of the PCMS

The virtual construction simulation system (VCS) comprises the application server (i.e., the virtual construction engine), the client end, the web server and the database server. The application server handles the business logic of the PCMS by monitoring three possible sources of danger, namely, a person falling from a height, striking against or being struck by moving objects, and being struck by moving vehicles. The system monitors the relative distances between the workers (represented by the positions of the tags installed on the helmets) and potential sources of danger (represented by the tags installed on the moving objects and danger zones that are dynamically defined in the 3D model of the construction site). If the detected distance between a worker and a nearby source of danger is equal to or less than an allowable value, a warning signal will be triggered and sent to the real time location

positions of the location tags are calculated by the location engine. Approximately 100 tags were installed on-site for around four months to evaluate the technical feasibility and usefulness of the PCMS. The construction site was separated into eight zones approximately 30m x 30m in size for the PCMS. Ranging results were sent to the location engine through the CSS wireless network. An example of an image captured by the PCMS system during the trial run for this project is shown in Figure 3. The red spot represents the location of the site operators while the blue spots represent the locations of the hook of the tower crane. The simulation results indicated that the project had no obvious site hazard black-spots.

In summary, the CO₂ emission prediction tool presented in this paper can help contractors to identify the sources of emissions and to quantify the amount of emissions generated. The tool also promotes a pro-active environmentally conscious construction approach and the best practices for sustainable development. The tool can assist builders/contractors to forecast activities with excessive emissions and identify suitable mitigation strategies, such as replacing old plant and equipment with energy-saving models and reducing idling time. The PCMS also provides a platform for the construction project team to reassess their site safety plan. The tool provides pro-active warnings to site workers and helps them to detect surrounding sources of danger, such as height hazards and materials being moved by the tower crane.



Figure 3. Location of the site operators (red spot) and the hook of the tower crane (blue spots) captured by the PCMS system

4 Conclusion and Future Research

This paper outlines the development and application of a 5D visualisation tool to support project teams in estimating and visualising the CO₂ emissions from construction activities and predicting potential hazard

black spots. Nonetheless, the 5D model is still in its preliminary stage and the tool needs to be applied to different construction projects of varying scale and nature. A comprehensive carbon footprint assessment tool is also required to predict the total embodied energy (including the carbon emitted from embodied energy and the building assembly process) of the project. An integrated life-cycle analysis (LCA) with BIM will be developed to monitor the embodied carbon [for example, 25 and 26]. A BIM based tool that can provide support for managing construction and demolition waste is currently lacking. The PCMS presented in this paper is also at the trial run stage, and the tool requires further testing and validation before it can be widely adopted on-site. These limitations will be tackled in future studies.

Acknowledgement

The authors would like to acknowledge the support of the Hong Kong Housing Authority in conducting this research.

References

- [1] Chan, A.P.C. and Chan, A.P.L. Key performance indicators for measuring construction success, *Benchmarking: An International Journal*, 11(2): 203-221, 2004.
- [2] Wong, J.K.W., Li, H., Wang, H., Huang, T., Luo, E., and Li, V. Toward low-carbon construction processes: the visualisation of predicted emission via virtual prototyping technology, *Automation in Construction*, 33:72-78, 2013
- [3] OSHB (Occupational Safety and Health Branch, Labour Department): Occupational Safety and Health Statistics 2009. www.labour.gov.hk/eng/osh/pdf/OSH_Statistics_2009.pdf, 2010
- [4] OSHB (Occupational Safety and Health Branch, Labour Department): Occupational Safety and Health Statistics 2010. www.labour.gov.hk/eng/osh/pdf/OSH_Statistics2010.pdf, 2011
- [5] HKSAR Government, The 2011-12 Policy Address, available at: <http://www.policyaddress.gov.hk/11-12/eng/pdf/Policy11-12.pdf> (accessed on 11/10/11), 2011
- [6] Artenian, A., Sadeghpour, F., and Teizer, J. A GIS framework for reducing GHG emissions in concrete transportation, In *Proc. of Construction Research Congress*, pages 1557-1566, Canada, May 10, 2010.
- [7] Ahn, C. and Lee, S.H. Importance of operational efficiency to achieve energy efficiency and exhaust emission reduction of construction operations, *Journal of Construction Engineering and Management*, ASCE, 139: 404-41, 2013

- [8] Ahn, C., Rekapalli, P.V., Martínez, J.C., and Peñá-Mora, F. Sustainability analysis of earthmoving operations, In *Proc. of Winter Simulation Conference*, pages 2605-2611, 2009.
- [9] Carmichael, D.G., Williams, E.H., and Kaboli, A.S. Minimum operational emissions in earthmoving, *Construction Research Congress 2012*: 1869–1878, 2012
- [10] Hajibabai, L., Aziz, Z. and Peñá-Mora, F. Visualizing greenhouse gas emissions from construction activities, *Construction Innovation*, 11(3): 356-370, 2011
- [11] Hasan, S., Bouferguene, A., Al-Hussein, M., Gillis, P., and Telyas, A. Productivity and CO2 emission analysis for tower crane utilization on high-rise building projects, *Automation in Construction*, 31: 255–264, 2013
- [12] Heydarian, A. and Golparvar-Fard, M. A visual monitoring framework for integrated productivity and carbon footprint control of construction operations, In *Proc. of the 2011 ASCE Int. Workshop on Computing in Civil Engineering*, pages 504-511, Miami, June, 2011
- [13] Lee, Y-S., Skibniewski, M.J. and Jang W-S. Monitoring and management of greenhouse gas emissions from construction equipment using wireless sensors, In *Proc. of the 26th Int. Symposium on Automation & Robotics in Construction*, pages 227-234, Texas, U.S. June 24-27, 2009
- [14] Lewis, M.P. *Estimating fuel use and emission rates of nonroad diesel construction equipment performing representative duty cycles*, PhD Dissertation, North Carolina State University, Raleigh, NC., 2009,
- [15] Peñá-Mora, F., Ahn, C., Golparvar-Fard, M., Hajibabai, L., Shiftehfar, S., An, S., and Aziz, Z. A framework for managing emissions from construction processes, In *Proc., Int. Conf. & Workshop on Sustainable Green Bldg. Design & Construction*, National Science Foundation. 2009
- [16] Sharrard, A.L., Matthews, H.S., and Roth, M. Environmental implications of construction site energy use and electricity generation, *Journal of Construction Engineering and Management*, 133: 846-854, 2007
- [17] Shiftehfar, R., Golparvar-Fard, M., Peñá-Mora, F., Karahalos, K.G., and Aziz, Z. The application of visualization for construction emission monitoring, In *Proc. of Construction Research Congress*, pages 1396-1405, Canada, May, 2010
- [18] Carbonari, A., Giretti, A., and Naticchia, B. A proactive system for real-time safety management in construction sites, *Automation in Construction*, 20(6): 686-698, 2011
- [19] Cheng, T. and Teizer, J. Real-time resource location data collection and visualization technology for construction safety and activity monitoring applications, *Automation in Construction*, 34: 3-15, 2012
- [20] Teizer, J., Cheng, T., and Fang, Y., Location tracking and data visualization technology to advance construction ironworkers' education and training in safety and productivity. *Automation in Construction*, 35: 53-68, 2013
- [21] Wu, W., Yang, H., Li, Q., and Chew, D. An integrated information management model for proactive prevention of struck-by-falling-object accidents on construction sites. *Automation in Construction*, 34: 67-74, 2013
- [22] Teizer, J., Allread, B. S., Fullerton, C. E., and Hinze, J. Autonomous pro-active real-time construction worker and equipment operator proximity safety alert system, *Automation in Construction*, 19(5): 630-640, 2010.
- [23] Chae, S. and Yoshida, T. Application of RFID technology to prevention of collision accident with heavy equipment, *Automation in Construction*, 19(3): 368-374, 2010
- [24] Hwang, S. Ultra-wide band technology experiments for real-time prevention of tower crane collisions, *Automation in Construction*, 22: 545-553, 2012
- [25] Guo, H.L., Li, H., and Skitmore, M. Life-cycle management of construction projects based on virtual prototyping technology, *Journal of Management in Engineering*, 26(1): 41-47, 2010
- [26] Guo, H.L., Li, H., and Li, V. VP-based safety management in large-scale construction projects: a conceptual framework, *Automation in Construction*, 34:16–24, 2013